

PRODUCT USAGE CHECKLIST



Available at:



3M Select.co.uk
The Official 3M
UK Online Store

3M™ PERFORMANCE FINISH | 39030

- Provides a long-lasting, high-gloss finish to paintwork
- Exceptional water beading qualities
- Synthetic polymers bond to the paint surface providing maximum protection

DIRECTIONS FOR USE:

(Do not apply in direct sunlight or onto a hot surface)

Wash and dry vehicle using 3M™ Car Wash Soap (PN 39000). If paint is dull or oxidized use 3M™ Scratch Remover (pn 39044) after washing the vehicle but prior to using 3M™ Performance Finish.

HAND

A

Gently apply a thin, uniform film to the paint surface using a terry cloth wax applicator or a clean, soft, folded cotton terry cloth towel

B

Remove residue and buff to a high gloss using a 3M™ Microfibre Detail Cloth (PN 39016) or a clean, soft, cotton terry cloth towel

C

Complete steps one panel at a time

MACHINE

A

Apply a thin uniform film to the paint surface using a random orbital polisher equipped with a clean, soft, terry cloth bonnet or a DA equipped with a soft foam pad

B

Buff to a high gloss with a polisher equipped with a clean, dry, terry cloth bonnet or by hand using a 3M™ Microfibre Detail Cloth (PN 39016) or a clean, soft, cotton terry cloth towel

C

Complete steps one panel at a time

www.3M.co.uk/carcare

A P P E A R A N C E